

HUBER+SUHNER® DATA SHEET

Coaxial Cable Connector: 11_QMA-50-2-3/133_N



Description

Straight cable plug for semi-rigid cable

Interface standards
SUHNER-QMA



Technical Data

Electrical Data

Impedance 50 Ω
Interface frequency max. 18 GHz

Mechanical Data

Centre contact plugged
Outer contact soldered
Weight 0.0044 kg

Environmental Data

Operating Temperature -40 °C to 85 °C

Material Data

Piece Parts

Centre contact	Copper Beryllium / Bronze
Outer contact	Bronze
Body	Brass
Insulator	PFA / PTFE

Surface Plating

SUCOPRO Plating
SUCOPLATE (R) Plating
SUCOPRO Plating

Related Documents

Outline drawing	DOU-00007073
Catalogue drawing	DOU-00007075
Assembly instruction	DOC-0000179521

Ordering Information

Single package	11_QMA-50-2-3/133_NE
Bulk 100 pcs package	11_QMA-50-2-3/133_NH

Additional Information

Suitable cables SUCOFORM_86, EZ_86_TP_M17, MULTIFLEX_86

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



HUBER+SUHNER AG
RF Technology
9100 Herisau, Switzerland
Phone +41 (0)71 353 41 11
Fax +41 (0)71 353 45 90
www.hubersuhner.com

HUBER+SUHNER – Excellence in Connectivity Solutions